

2014 NS-BIKES WHEELBUILDING INFO

What spoke lengths do I need to use with NS hubs / rims?

Please look up the hub / rim that you are interested in. You will find all the info for spoke calculators.

One of them that you can use is on www.dtswiss.com

RIMS

RIM MODEL	Diameter / ERD [mm]	OFFSET* [mm]
Enigma 26"	529	0
Fundamental 26"	542	2
Trailmaster 2 / 1 26"	542	2
Fudnamental 24"	490	2
Trailmaster 2 / 1 26"	490	2

* Asymmetrical spoke drilling - offset from the center of the rim. No significant influence while calculating the correct spoke length

all NS rims are designed for standard 3 cross lacing

HUBS

HUB MODEL	P.C.D LEFT [mm]	P.C.D RIGHT [mm]	LEFT-CENTER [mm]	RIGHT-CENTER [mm]	O.L.D [mm]
2014-2011 Rotary 10	38	38	31	31	100
2014-2011 Rotary 20	47	47	34	34	110
2014-2011 Rotary 20 disk	58	49	22	34	110
2014-2011 Rotary Cassette 135x10, 142x12/135x12	58	49	34	21	135/142
2014 Rotary Cassette 157x12/150x12	58	49	41	29	150/157
2014-2011 Rotary Single	58	49	34	38	135
2014-2011 Rotary Single Pro	58	51	34	38	135
2010 Rotary 10	38	38	31	31	100
2010 Rotary 20	47	47	29	29	110
2010 Primary 20	58	49	22	34	110
2010 Primary Cassette	58	49	34	21	135
2010 Primary Single	58	49	34	38	135
2010 Rotary rear	58	58/51*	34	38	135
Roller simple 10	47	47	32	32	100
Roller simple 20	49	49	34	34	110
Roller 20 disk	58	49	22	34	110
Coaster	58	58	34	21	135
Coaster Pro	58	54	34	21	135
Coaster SS	58	58	35	40	135
Coaster SS Pro	58	58	34	38	135

* pls check your version size

P.C.D: Pitch Circle Diameter [left & right flange size]

LEFT-CENTER / RIGHT-CENTER: distance between the left / right flange and the center of the hub

OLD: Outer Locknut Dimension [overall width of the hub]

spoke holes diameter: $\varnothing \approx 2.5\text{mm}$

all NS Bikes hubs are available in 32 and 36 spoke holes version